

**Materials and colours**

opaline glass cylinder with metal black varnished stem

NOTE: the stems of the Syphasera collection are made of metal protected for outdoor with black coloured varnish. In case of installation into water, we recommend a version available on request designed for this kind of projects and requests.

**Light source**


LED bulb G4 12V DC 1x max 1W / energy class G / lumen 75 / K 2700 / CRI 80 / protection grade IP65

NOTE: IP specifics - lamp holder IP65 (not protected against immersion); wires and connectors IP68; drivers IP67; IP average rate of the lamp 44.

**Power supply**

12V DC transformer not included

## Dimensions



cylinder with holder  
Ø 1,5 x H 21 cm  
H tot. 65 cm (cable 255 cm)  
H tot. 80 cm (cable 240 cm)  
H tot. 110 cm (cable 210 cm)  
H tot. 140 cm (cable 180 cm)

---

## Order code

SYS65 H 65 cm  
SYS80 H 80 cm  
SYS110 H 110  
cm  
SYS140 H 140  
cm

---

## Accessories for gel box system

ED6 driver 10W 12V DC 220-240V IP67 not dimmable (max 6 lamps)  
MB1 mini gel box IP68 (max 2 connections, connector included)  
MB2 mini gel box IP68 (max 6 connections, connector included)  
KP1 extension kit 5 mt with mini gel box IP68 (max 1 lamp)

---

## Accessories for quick connectors system

ED6CR driver 10W 12V DC 220-240V IP67 not dimmable with quick connectors (max 6 lamps)  
CRM multiple quick connector IP68 - 1 IN & 5 OUT (max 5 connections)  
CRS single quick connector IN IP68  
KP2 extension kit 5 mt with quick connectors IP68 (max 1 lamp)